



# Refining High Performance FORTRAN Code from Programming Model Dependencies

Ferosh Jacob<sup>1</sup>, Jeff Gray<sup>1</sup>, Purushotham Bangalore<sup>2</sup>, Marjan Memik<sup>32</sup>


<sup>1</sup>Department of Computer Science, University of Alabama

<sup>2</sup>Department of Computer and Information Sciences, University of Alabama at Birmingham

<sup>3</sup>Faculty of Electrical Engineering and Computer Science, University of Maribor


Contact: fjacob@crimson.ua.edu

### **Challenges in Parallel Programming**



The execution plot of the satisfiability problem in Figure 1 shows that even though the performance of OpenMP and MPI are comparable, for small problems the OpenMP version is faster than an MPI solution. In cases where the size of the data varies, different versions of the same program might be required if a single HPC library is used.

# Architecture Dependencies in Parallel Programming



Manually maintaining such variations induces unnecessary redundant effort that is also very prone to human errors in maintaining and updating the core algorithms. Therefore, the development of an HPC program is often limited to a specific parallel library. Otherwise, the programmer pays the price of developing and maintaining several versions of the same program.

# Program Analysis of FORTRAN OpenMP Programs


No	Program Name	Total LOC	Parallel LOC	No. of blocks	R	W
1	2D Integral with Quadrature rule	601	11 (2%)	1	<b>√</b>	
2	Linear algebra routine	557	28 (5%)	4		√
3	Random number generator	80	9 (11%)	1		
4	Logical circuit satisfiability	157	37 (18%)	1	<b>√</b>	
5	Dijkstra's shortest path	201	37 (18%)	1		
6	Fast Fourier Transform	278	51 (18%)	3		
7	Integral with Quadrature rule	41	8 (19%)	1	<b>√</b>	
8	Molecular dynamics	215	48 (22%)	4	<b>√</b>	√
9	Prime numbers	65	17 (26%)	1	<b>√</b>	
10	Steady state heat equation	98	56 (57%)	3	√ √	

Shared memory features	Parallel features			
Variable modifiers, Critical	Parallel blocks, Reduction			
and Singular blocks,	and Barrier blocks,			
Number of threads	Number of instances,			
	Workshare			

#### **Analysis Conclusion**

A DSL that uses only the parallel features can express parallel problems in a platform-independent manner. Most of the programs involve an initialization segment that initializes the execution of the parallel part, and a code segment that is used to collect data from the parallel instances

## Proposed Approach to Express Parallel Programs in FORTRAN



### **MPI Case Study**

```
!Part 1: Master process setting up the data
if (my id == 0) then do p = 1, p = 1
     my a = (real (p num - p, kind = 8) * a &
           + \text{ real } ( p - 1, kind = 8) * b) &
            / \text{ real (p num} - 1, kind = 8)
     target = p
     tag = 1
     call MPI Send ( my a, 1, MPI DOUBLE PRECISION, &
                    target, tag, &MPI COMM WORLD, &
                    error flag )
   end do
!Part 2: Parallel execution
 else
   source = master
   taq = 1
   call MPI Recv ( my a, 1, MPI DOUBLE PRECISION, source, tag,
     MPI COMM WORLD, status, error flag )
   my total = 0.0D+00
   do i = 1, my n
     x = (real (my n - i, kind = 8) * my a &
        + \text{ real } ( i - 1, \text{ kind } = 8) * \text{ my b} ) &
         / \text{ real (my n} - 1, \text{ kind} = 8)
     my total = my total + f(x)
   end do
   my total = ( my b - my a ) * my total / real
                                       (myn, kind = 8)
 end if
!Part 3: Results from different processes are collected to
! calculate the final result
 call MPI Reduce ( my total, total, 1,
                   MPI DOUBLE PRECISION, & MPI SUM,
                   master, MPI COMM WORLD, error flag)
```

```
!Work share part
   do p = 1, instance num - 1
     my a = (real (instance num - p, kind = 8) * a &
            + \text{ real } ( p - 1, kind = 8) * b) &
            / real ( instance num - 1, kind = 8 )
     call distribute (my a)
    end do
!Declaring parallel block
 call parallel(num,'quadrature')
   my total = 0.0D+00
   do i = 1, my n
     x = (real (my n - i, kind = 8) * my a &
         + real ( i - 1, kind = 8) * my b) &
         / \text{ real (my n} - 1, \text{ kind} = 8)
     my total = my total + f (x)
   end do
    my total = ( my b - my a ) * my total / real
                                      (myn, kind = 8)
 call endparallel('quadrature');
! Configuration file for FORTRAN program above
block 'quadrature'
init:
   source = master
   tag = 1
   call MPI Recv ( my a, 1, MPI DOUBLE PRECISION, source, tag,
     MPI COMM WORLD, status, error flag ).
call MPI Reduce ( my total, total, 1,
                   MPI DOUBLE PRECISION, & MPI SUM,
                   master, MPI COMM WORLD, error flag).
distribute param:
      call MPI Send ( param, 1, MPI DOUBLE PRECISION, &
                   target, tag, &MPI COMM WORLD, &
                    error flag ).
```

#### **Conclusion and Future Work**

#### **Conclusion:**

For the evolution of high performance FORTRAN code, it is necessary to separate the code of **the core computation** from the **machine or architecture dependencies** that may come from usage of a specific API.

We **analyzed** ten FORTRAN programs from diverse domains to understand the usage of OpenMP in scientific code. The analysis revealed that programs often share a common structure such that platform and machine details could be specified in a different file.

A case study is included to show that the approach can be extended to other architectures.

#### **Future work:**

Includes **refactoring the legacy code** to the approach specified in this paper with minimum input from the user. Another direction will be focused on executing the **parallel programs to a GPU**. Conducting a **user study** to explore the advantages and disadvantages from a human factors perspective is another direction of work.

### Thank You

Questions?

Ferosh Jacob<sup>1</sup>, Jeff Gray<sup>1</sup>, Purushotham Bangalore<sup>2</sup>, Marjan Memik<sup>32</sup>

<sup>1</sup>Department of Computer Science, University of Alabama <sup>2</sup>Department of Computer and Information Sciences, University of Alabama at Birmingham <sup>3</sup>Faculty of Electrical Engineering and Computer Science, University of Maribor

Contact: fjacob@crimson.ua.edu